

## MB AM5 GIGABYTE B650I AX Rev 1.0

Šifra: 93417

Kategorija proizvoda: Matične ploče

Proizvođač: GIGABYTE

Cena: **19.000,00**



### CPU

AMD Socket AM5,  
support for: AMD  
Ryzen™ 7000 / Ryzen™  
8000 / Ryzen™ 9000  
Series Processors

(Please refer "CPU Support List" for more information.)

### Chipset

AMD B650

### Onboard Graphics

Integrated Graphics Processor:

1 x DisplayPort,  
supporting a maximum  
resolution of  
3840x2160@144 Hz  
\* Support for DisplayPort  
1.4 version.

1 x HDMI port,  
supporting a maximum  
resolution of  
4096x2160@60 Hz  
\* Support for HDMI 2.1  
version and HDCP 2.3.  
\*\* Support native HDMI  
2.1 TMDS compatible  
ports.

(Graphics specifications may vary depending on CPU support.)

### LAN

Realtek® 2.5GbE LAN  
chip (2.5 Gbps/1  
Gbps/100 Mbps)

### Memor

Supp  
6400  
6000  
5200  
mem

### Audio

Realt

(The CI  
suppor  
numbe  
Suppor

### Wireles

Realtek® Wi-Fi 6E RTL8852CE

WIFI a, b, g, n, ac, ax,  
supporting 2.4/5/6 GHz  
carrier frequency bands

BLUETOOTH 5.3

Support for 11ax  
160MHz wireless  
standard

(Actual data rate may vary depending on environment  
and equipment.)

Expansion Slots

1 x PCI Express x16 slot, integrated in the CPU:

AMD Ryzen™ 7000  
Series Processors/  
Ryzen™ 9000 Series  
Processors support PCIe  
4.0 x16 mode

AMD Ryzen™ 8000  
Series-Phoenix 1  
Processors support PCIe  
4.0 x8 mode

AMD Ryzen™ 8000  
Series-Phoenix 2  
Processors support PCIe  
4.0 x4 mode

\* The PCIEX16 slot can  
only support a graphics  
card or an NVMe SSD.

Storage

1 x M.2

Socket

AMD

Series

Ryzen

Proce

4.0 x

USB

CPU:

1 x USB Type-C® port on  
the back panel, with USB  
3.2 Gen 1 support

1 x USB 3.2 Gen 2 Type-  
A port (red) on the back  
panel

1 x USB 2.0/1.1 port on  
the back panel

2 x SATA

RAID 0

devices

internal

RAID 0

Chipset:

1 x USB Type-C® port  
with USB 3.2 Gen 1  
support, available  
through the internal USB  
header

3 x USB 3.2 Gen 1 ports  
(1 port on the back  
panel, 2 ports available  
through the internal USB  
header)

4 x USB 2.0/1.1 ports (2  
ports on the back panel,  
2 ports available  
through the internal USB  
header)

1 x 24-pin ATX main power connector	1 x 8-pin ATX 12V power connector 1 x CPU fan header  2 x system fan headers 1 x addressable LED strip header 1 x RGB LED strip header	Back Panel Connectors 1 x DisplayPort	1 x HDMI port 1 x USB Type-C® port, with USB 3.2 Gen 1 Type-A support (red)  1 x USB 3.2 Gen 1 port	I/O Connector iTE®
	1 x M.2 Socket 3 connector, SATA 6Gb/s connectors 1 x front panel header  1 x front panel audio header 1 x speaker header  1 x USB Type-C® header with USB 3.2 Gen 1 support 1 x USB 2.0/1.1 header  1 x Clear CMOS jumper 1 x chassis intrusion header		3 x USB 2.0/1.1 ports 1 x Q-Flash Plus button 1 x RJ-45 port 2 x SMA antenna connectors (2T2R) 3 x audio jacks	
		H/W Monitoring Voltage detection	Temperature detection Fan speed detection Water cooling flow rate detection Fan fail warning  Fan speed control * Whether the fan speed control function is supported will depend on the fan you install.	BIOS 1 x 2
		Unique Features Support for GIGABYTE Control Center (GCC) * Available applications in GCC may vary by motherboard model. Supported functions of each application may also vary depending on motherboard specifications.	Support for Q-Flash  Support for Q-Flash Plus	Bundle Norton Security
		Operating System Support for Windows 11 64-bit	Support for Windows 10 64-bit	Form Factor Mini-ITX 17.0cm