

MB s1700 ASUS ROG STRIX B760-F GAMING WIFI

Šifra: 94734

Kategorija proizvoda: Matične ploče

Proizvođač: ASUS

Cena: 30.370,00



Osnovne karakteristike

Procesorsko ležište (socket)	Intel 1700
Čipset	Intel B760
Memorija	
Tip memorije	DDR5
Memorijski slotovi	4
Podržane memorije	6.000MHz (O.C.), 5.800MHz (O.C.), 6.200MHz (O.C.), 4.800MHz, 6.400MHz (O.C.), 5.200MHz, 5.000MHz, 5.600MHz, 5.400MHz, 6.800MHz (O.C.), 7.000MHz (O.C.), 7.800MHz (O.C.)
Maksimalna ukupna memorija	192GB
Ostale osobine	Podrška za Extreme Memory Profile (XMP), Podrška za non-ECC UDIMM memory, OptiMem II

Slotovi

PCI Express x16 slot	1x PCI Express 3.0 (x4 mode), 1x PCI Express 5.0 (x16 mode)
PCI Express x1 slot	2x PCI Express 3.0
Ostali slotovi	3x M.2 slot, 4x SATA 6.0Gb/s ports

Skladišni interfejsi

SATA priključci (ukupno)	4
SATA priključci	SATA III 6Gbps
Broj M.2 slotova	3
RAID	RAID 0, RAID 1, RAID 5, RAID 10

Mreža

Žična mreža (LAN)	2.5GBase-T (Gigabit)
Model	Intel
Wi-Fi	Da
Wi-Fi standard	Wi-Fi 6E (802.11ax)
Bluetooth	Da
Bluetooth verzija	5.3

Audio

Broj kanala	8 (7.1)
Model	ROG SupremeFX
Napomena	Jack-detection, Multi-streaming, Front Panel Jack-retasking, Premium audio capacitors, SupremeFX Shielding, Savitech SV3H712 AMP

Priključci na zadnjem panelu

Broj DisplayPort priključaka	1
Broj HDMI priključaka	1
Ukupno USB priključaka	8
Ukupno USB-C priključaka	1
USB-A priključci	1x USB 10Gbps (3.2 Gen 2), 6x USB 5Gbps (3.2 Gen 1)

USB-C priključci	1x USB 20Gbps (3.2 Gen 2x2)
RJ-45 (LAN)	1
Audio	5x 3.5mm
Ostali priključci	Clear CMOS prekidač, Clear CMOS button(s), 1 x optical S/PDIF, USB BIOS Flashback Button(s)

Unutrašnji priključci

Naponski priključci	1x 4 pin 12V Power Connector, 1 x 24 pin Main Power connector, 1 x 8-pin ATX 12V power connector
USB-A	1 x podrška za 4 USB 2.0 porta, 1 x podrška za 2 USB 5Gbps porta
USB-C	1 x podrška za 1 USB 10Gbps port
Audio	1x Front panel audio
Ostali priključci	3x M.2 Socket 3, 1 x Thunderbolt header(s), 1 x 4-pin AIO Pump header, 1 x 4-pin CPU OPT Fan header, 1 x 20-3 pin System Panel header with Chassis intrude function, 1 x 4-pin Chassis Fan header, 1 x 4-pin CPU Fan header, 3 x Addressable Gen 2 headers, 1 x AURA RGB header, 1 x Thermal Sensor header, 2 x SATA 6Gb/s
Napomena	Za iskorišćavanje određenih internih konektora potrebni su dodatni bracket-i ili priključci na kućištu

Ostale karakteristike

Podržane tehnologije	AURA Creator, AURA Sync, Fan Xpert 4, DIGI+VRM, ASUS CrashFree BIOS 3, ASUS EZ Flash 3, SafeSlot, Q-DIMM, Q-Slot, Q-LED Core, PC Cleaner, SafeDIMM, ProCool, UEFI Bios, Sonic Radar III, Sonic Studio III, ROG CPU-Z, VRM heatsink design, Extreme Engine Digi+, Aura RGB header, DTS Sound Unbound, GameFirst VI, BIOS FlashBack button, BIOS FlashBack LED
----------------------	--

Fizičke karakteristike

Format	ATX
Dimenzije	305mm x 244mm
Pakovanje	Full box retail
Reklamacioni period	
Reklamacioni period	36 meseci